

Construction: 105/80

Applicable for product codes: 11

1l frame	Width mm	Height mm	Max W+H mm	Max weight kg
	588 – 1188	1338 – 2537	3500	
AB	688 – 1188	1338 – 2537	3500	
VLD319 - Center lock positioned 1000mm up from underside threshold	588 – 1188	1888 – 2488		

1l sash	Width mm	Height mm	Max W+H mm	Max weight kg
	511 – 1111	1286 – 2485	3476	120
AB	611 – 1111	1286 – 2485	3476	
VLD319 - Center lock positioned 1000mm up from underside threshold	511 – 1111	1836 – 2436		
VLD891 - SBD	511 – 1111	1886 – 2485		

Remarks

1l frame

- # NorDan Security balcony door - standard pack:
 With thumbturn internally and blankplate externally (sent loose).
 Espagnolette consists of a security lock in the center, 3 tightening tonques, center hook bolt and sprung latch.
 Frame height < 1938 mm: 2 locking points on espagnolette.
- # Standard with 3 hinges:
 Frame width >= 1043 mm : 4 no. hinges
 Frame heigh >= 2389 mm : 4 no. hinges
 Sash weight >= 85 kg : 4 no. hinges
- # Clear opening width calculation:

	Without aluminium	With aluminium
Opened 90 degrees; Frame width minus:	211 mm	225 mm
Opened 180 degrees; Frame width minus:	112 mm	125 mm