

# SD 2P SLIDING SINGLE DOOR

SLIDE TO SIDE



**Glides smoothly on sealed ball bearings set safely beneath the door, making it easy to open and close even in larger dimensions. When the handle is turned up, the door moves out and away from the seal.**

With the right options this product can reach following parameters

**Weather performance**

> 98.92 mph

**Burglar resistance**

PAS24:2016

**Life expectancy**

> 60 years

**Sound Reduction**

> Up to 37 Rw + Ctr

**U-value**

> 0,9 Wm<sup>2</sup>/K

## Technical specification

<b>Glass (double)</b>	6-16G-ES4
<b>Glass (triple)</b>	4ES-16G-4-16G-ES4
<b>Exterior material</b>	Timber / Aluminium clad timber
<b>Interior material</b>	Timber
<b>Child safety</b>	N/A
<b>Escape route</b>	Yes
<b>Ventilation</b>	Yes
<b>Burglar resistance</b>	Yes, Secured by Design accredited
<b>Timber protection</b>	Yes, vacuum impregnated
<b>Ironmongery</b>	Assa / NorDan

## Product features

<b>Energy saving</b>	U-value: 0,8 to 1.3 W/m <sup>2</sup> K
<b>Entry sound reduction</b>	Rw 35dB Rw+Ctr 33dB
<b>Fire resistance</b>	-
<b>Watertightness</b>	Class 9A, EN 12208
<b>Passive availability</b>	N/A

Measure	Timber	Aluclad
Frame width	164 mm	172 mm
Min Width	1 388 mm	1 388 mm
Max Width	3 988 mm	3 988 mm
Min Height	1 650 mm	1 650 mm
Max Height	2 588 mm	2 588 mm
Width + Height	Max: 6 676 mm	Max: 6 676 mm
Sash weight	Max: 150 kg	Max: 150 kg

### 92 Timber



### 100 Aluclad



### 105 Timber



### 113 Aluclad

