



Well balanced ironmongery ensures the frame can easily be turned 180 degrees for safe cleaning from the inside of your building. The window has a child safety restrictor integrated in the hinges

With the right options this product can reach following parameters

Burglar resistance

> PAS24:2016

Life expectancy

> 60 years

Sound Reduction

> Up to 40dB Rw+Ctr

U-value

> 0,8 Wm²/K

Technical specification

Glass (double)	6-16G-ES4
Glass (triple)	4ES-16G-4-16G-ES4
Exterior material	Timber / Aluminium clad timber
Interior material	Timber
Child safety	Yes
Escape route	Yes
Ventilation	Yes
Burglar resistance	Yes, Secured by Design
Timber protection	Yes, vacuum impregnated
Ironmongery	NorDan TopTech

Product features



Energy saving	U-value 0.8 to 1.2 Wm ² /K
Cleaning	Cleaning from inside
Entry sound reduction	Rw 36dB Rw+Ctr 32dB
Fire resistance	-
Watertightness	Class 9A, EN 12208
Passive availability	Yes

Measure	Timber	Aluclad	Timber	Aluclad
Frame width	92 mm	100 mm	105 mm	113mm
Min Width	348 mm	348 mm	348 mm	348 mm
Max Width	2 388 mm	2 388 mm	2 388 mm	2 388 mm
Min Height	388 mm	388 mm	450 mm	450 mm
Max Height	1 788 mm	1 788 mm	1 788 mm	1 788 mm
Width + Height	Max: 3400 mm	Max: 3400 mm	Max: 3400 mm	Max: 3400 mm
Sash weight	Max: 80 kg	Max: 80 kg	Max: 80 kg	Max: 80 kg


92 Timber



92 mm





103 mm




100 Aluclad



100 mm





103 mm




105 Timber



105 mm




103 mm




113 Aluclad



113 mm



104 mm



106 mm

103 mm

