

OD ZD ONE TILT & TURN

INWARD OPENING



Single handle with multiple locking points, the window can be easily used for ventilation and opening into the cleaning position so the external glass can be safely cleaned from the inside.

With the right options this product can reach following parameters

Weather performance

> 127.7 mph wind load

Burglar resistance

> PAS24:2016

Life expectancy

> 60 years

Sound Reduction

> Up to 38dB $R_w + C_{tr}$

U-value

> 0,7 Wm^2/K



Technical specification

Glass (double)	6-16G-ES4
Glass (triple)	4ES+16G+4+16G+ES4
Exterior material	Timber / Aluminium clad timber
Interior material	Timber
Child safety	Yes, optional
Escape route	Yes, size permitted
Ventilation	Yes
Burglar resistance	PAS24:2016 (Secure By Design)
Timber protection	Yes, vacuum impregnated
Ironmongery	Roto

Product features

Energy saving	0,7-1,2 W/m ² K
Cleaning	Cleaning from inside
Entry sound reduction	Rw+Ctr 28 to 38
Fire resistance	-
Watertightness	Class 9A, EN 12208
Passive availability	Yes



Measure

	 Timber	 Aluclad
Frame width	105 mm	113mm
Min Width	488 mm	488 mm
Max Width	1 483 mm	1 483 mm
Min Height	488 mm	488 mm
Max Height	2 588 mm	2 588 mm
Width + Height	Max: 3 888 mm	Max: 3 888 mm
Sash weight	Max: 120 kg	Max: 120 kg


105 Timber



105 mm




94 mm




113 Aluclad



113 mm



105 mm



101 mm

94 mm

