



NorDan AB
 Grebbestadsvägen 8
 SE 457 91 Tanumshede
info@nordan.se
www.nordan.se

Declaration of performance: DoP-NDAB-NDKF-001v1-UK

In accordance CPR (Construction Products Regulation) 305/2011, we hereby declare that following products as NorDan products as shown in table 1, being manually operated windows/doors for fitting in domestic and commercial buildings and produced by:

- NorDan AS Stasjonsvein 46 N-4460 Moi. Norway
- NorDan AS. Skansen, N-2670 Otta. Norway
- NorDan AS. N-2266 Arneberg. Norway
- NorDan AS Tengsareidveien 1, N-4373 Egersund. Norway
- NorDan AB Kvadervägen 1, SE-330 15 Bor. Sweden.
- NorDan AB Fröreda 228 SE-574 55 Kvillsfors. Sweden.
- NorDan AB Grebbestadsvägen 8, SE-457 91 Tanumshede. Sweden
- NorDan SP.zo.o. UL. Fabryczna 16, 64-200 Wolsztyn, Poland
- NorDan SP.zo.o. UL. Powodowo 54, 64-200 Wolsztyn, Poland

- are in accordance with product standard EN 14351:2006 + A2: 2016 declared using system of attestation 3 in annex ZA.2 of EN 14351:2006 + A2: 2016 and verified by assessment and ITT by the following notified bodies:

- Rise Research Institutes of Sweden (nr 0402)
- British Board of Agrément (nr 0836)
- SINTEF Building and Infrastructure (nr 1071)

Table 1: **KT 991** Inward opened window – side hinge **ES** , Bottom hinge **EU**, Kipp-Dreh **EN**

Characteristic	
Resistance to wind load Test pressure (EN 12210:1999)	Class 3
Resistance to wind load Frame deflection (EN 12210:1999)	Class C
Water tightness (EN 12208:1999)	Class 9A
Load-bearing capacity of safety devices (threshold 350N)	Threshold
Thermal transmittance U_w (EN ISO10077-1:2006 & EN ISO 10077-2:2012) (W/m ² K) *	1,1
Solar energy transmisson % (EN 410:2011)	60%
Light transmission % (EN 410:2011)	75%
Air permeability (EN 12207:1999)	Class 4
Acoustic performance (EN ISO 140-3:1995) *	$R_w = 34dB$
# Fire resistance (EN 13501-2:2016)	E130

* Based on reference size 1230x1480mm with glass plc4 -16SwU+arg – plc4 – 16SwU+arg - XN4

-and that the products shown in table 1 conform to the essential characteristic performance indicated. This declaration of performance is issued under sole responsibility of the manufacturer.

For NorDan AB:

Andreas Palmquist.
 Product Development Kvillsfors Serien
 SE Kvillsfors 27/2-2020