

Limit values - ND NTech One Sidehinged



Document ID: 000F50(1.05)

Date: 18 November 2025

Page: 1 of 2

Construction: 105/80

Applicable for product codes: ZS

| ZS frame | Width mm | Height mm | Max W+H mm | Max weight kg |
|----------|-------------|--------------|---------------|------------------|
| | 488 - 1483 | 381 - 2588 | 3888 | |

| ZS sash | Width mm | Height mm | Max W+H mm | Max weight kg |
|--|-------------|--------------|---------------|------------------|
| | 424 - 1419 | 406 - 2506 | 3742 | 120 |
| VLD381 - Casementstay (window) | 509 - 1419 | 299 - 2506 | 3742 | 120 |
| VLD556 - Integrated ventilation stay | 504 - 1419 | 406 - 1518 | 3742 | 120 |
| VLD556&VLD891 | 546 - 1419 | 406 - 2506 | 3742 | 120 |
| VLD574 - Handle in bottom | 504 - 1519 | 406 - 1518 | 3742 | 120 |
| VLD691 - Magnetic switch ROTO | 424 - 1419 | 470 - 2506 | 3742 | 120 |
| VLS050 - Lowered by 50mm VLS075 - Lowered by 75mm | 424 - 1419 | 831 - 2506 | 3742 | 120 |
| VLS100 - Lowered by 100mm | 424 - 1419 | 752 - 2506 | 3742 | 120 |
| VLS125 - Lowered by 125mm | 424 - 1419 | 802 - 2506 | 3742 | 120 |
| VLS150 - Lowered by 150mm | 424 - 1419 | 852 - 2506 | 3742 | 120 |
| VLS175 - Lowered by 175mm | 424 - 1419 | 902 - 2506 | 3742 | 120 |
| VLS200 - Lowered by 200mm | 424 - 1419 | 952 - 2506 | 3742 | 120 |
| VLS225 - Lowered by 225mm | 424 - 1419 | 1002 - 2506 | 3742 | 120 |
| VLS250 - Lowered by 250mm | 424 - 1419 | 1052 - 2506 | 3742 | 120 |
| VLS275 - Lowered by 275mm | 424 - 1419 | 1102 - 2506 | 3742 | 120 |
| VLS300 - Lowered by 300mm | 424 - 1419 | 1152 - 2506 | 3742 | 120 |
| VLS325 - Lowered by 325mm | 424 - 1419 | 1202 - 2506 | 3742 | 120 |
| VLS350 - Lowered by 350mm | 424 - 1419 | 1252 - 2506 | 3742 | 120 |
| VLS375 - Lowered by 375mm | 424 - 1419 | 1302 - 2506 | 3742 | 120 |
| VLS400 - Lowered by 400mm | 424 - 1419 | 1352 - 2506 | 3742 | 120 |
| VLS425 - Lowered by 425mm | 424 - 1419 | 1402 - 2506 | 3742 | 120 |
| VLS450 - Lowered by 450mm | 424 - 1419 | 1452 - 2506 | 3742 | 120 |
| VLS475 - Lowered by 475mm | 424 - 1419 | 1502 - 2506 | 3742 | 120 |
| VLS500 - Lowered by 500mm | 424 - 1419 | 1552 - 2506 | 3742 | 120 |
| VLS525 - Lowered by 525mm | 424 - 1419 | 1602 - 2506 | 3742 | 120 |
| VLS550 - Lowered by 550mm | 424 - 1419 | 1652 - 2506 | 3742 | 120 |

| ZS sash Illegal interval ranges | Width mm | Height mm | Max W+H mm | Max weight kg |
|------------------------------------|-------------|--------------|---------------|------------------|
| VLD556&VLD891 VLD556 | 424 - 800 | 406 - 950 | 3742 | 120 |

Limit values - ND NTech One Sidehinged



Document ID: 000F50(1.05)

Date: 18 November 2025

Page: 2 of 2

Construction: NTech Passive

Applicable for product codes: ZS

| ZS frame | Width mm | Height mm | Max W+H mm | Max weight kg |
|----------|-------------|--------------|---------------|------------------|
| | 488 - 1483 | 381 - 2588 | 3888 | |

| ZS sash | Width mm | Height mm | Max W+H mm | Max weight kg |
|--|-------------|--------------|---------------|------------------|
| | 424 - 1419 | 406 - 2506 | 3742 | 120 |
| VLD381 - Casementstay (window) | 509 - 1419 | 299 - 2506 | 3742 | 120 |
| VLD556 - Integrated ventilation stay | 636 - 1419 | 406 - 2506 | 3742 | 120 |
| VLD556&VLD891 | 546 - 1419 | 406 - 2506 | 3742 | 120 |
| VLD574 - Handle in bottom | 504 - 1419 | 406 - 1518 | 3742 | 120 |
| VLD691 - Magnetic switch ROTO | 424 - 1419 | 470 - 2506 | 3742 | 120 |
| VLS050 - Lowered by 50mm VLS075 - Lowered by 75mm | 424 - 1419 | 831 - 2506 | 3742 | 120 |
| VLS100 - Lowered by 100mm | 424 - 1419 | 752 - 2506 | 3742 | 120 |
| VLS125 - Lowered by 125mm | 424 - 1419 | 802 - 2506 | 3742 | 120 |
| VLS150 - Lowered by 150mm | 424 - 1419 | 852 - 2506 | 3742 | 120 |
| VLS175 - Lowered by 175mm | 424 - 1419 | 902 - 2506 | 3742 | 120 |
| VLS200 - Lowered by 200mm | 424 - 1419 | 952 - 2506 | 3742 | 120 |
| VLS225 - Lowered by 225mm | 424 - 1419 | 1002 - 2506 | 3742 | 120 |
| VLS250 - Lowered by 250mm | 424 - 1419 | 1052 - 2506 | 3742 | 120 |
| VLS275 - Lowered by 275mm | 424 - 1419 | 1102 - 2506 | 3742 | 120 |
| VLS300 - Lowered by 300mm | 424 - 1419 | 1152 - 2506 | 3742 | 120 |
| VLS325 - Lowered by 325mm | 424 - 1419 | 1202 - 2506 | 3742 | 120 |
| VLS350 - Lowered by 350mm | 424 - 1419 | 1252 - 2506 | 3742 | 120 |
| VLS375 - Lowered by 375mm | 424 - 1419 | 1302 - 2506 | 3742 | 120 |
| VLS400 - Lowered by 400mm | 424 - 1419 | 1352 - 2506 | 3742 | 120 |
| VLS425 - Lowered by 425mm | 424 - 1419 | 1402 - 2506 | 3742 | 120 |
| VLS450 - Lowered by 450mm | 424 - 1419 | 1452 - 2506 | 3742 | 120 |
| VLS475 - Lowered by 475mm | 424 - 1419 | 1502 - 2506 | 3742 | 120 |
| VLS500 - Lowered by 500mm | 424 - 1419 | 1552 - 2506 | 3742 | 120 |
| VLS525 - Lowered by 525mm | 424 - 1419 | 1602 - 2506 | 3742 | 120 |
| VLS550 - Lowered by 550mm | 424 - 1419 | 1652 - 2506 | 3742 | 120 |

| ZS sash | Width mm | Height mm | Max W+H mm | Max weight kg |
|-------------------------|-------------|--------------|---------------|------------------|
| Illegal interval ranges | | | | |
| VLD556&VLD891 | 424 - 800 | 929 - 950 | 3742 | 120 |
| VLD556 | 424 - 800 | 406 - 950 | 3742 | 120 |